

目盛付スチールビームトランメル OS-162 GRADUATED STEEL BEAM TRAMMEL OS-162



● OS-162 寸法表 Dimensions OS-162

No.	呼称法 Nominal size (mm)	ビーム長 Beam length (mm)	巾 Width (mm)	厚 Thickness (mm)	ポイント Point φ (mm)	製品質量 Weight (kg)
1	300	390	20	4	6.8 × 70	1.5
2	500	660	30	6	9 × 72	2.5
3	1000	1165	30	6	9 × 72	4
4	1500	1665	32	6	9 × 72	6
5	2000	2165	40	8	12 × 100	12
6	3000	3165	50	10	12 × 100	21

スチールビームトランメル OS-163 STEEL BEAM TRAMMEL OS-163



● OS-163 寸法表 Dimensions OS-163

No.	呼称法 Nominal size (mm)	ビーム長 Beam length (mm)	本体直径 Diameter of the main unit φ (mm)	ポイント Point φ (mm)	製品質量 Weight (kg)
1	500	600	25.4	15 × 70	1
2	1000	1100	25.4	15 × 70	3
3	1500	1600	25.4	15 × 70	4.5
4	2000	2100	25.4	15 × 70	6.5
5	3000	3100	31.8	15 × 70	16
6	4000	4100	31.8	15 × 70	21

サーフェスゲージ(トースカン) OS-164 SURFACE GAUGE OS-164

● OS-164 寸法表 Dimensions OS-164



No.	高さ Height (mm)	角台 Square stand		丸台 Round stand		
		台長 × 巾 × 高 Stand length × Width × Height (mm)	製品質量 Weight (kg)	柱径 Pole diameter φ (mm)	台径 × 高 Stand diameter × Height φ (mm)	製品質量 Weight (kg)
1	150	70 × 45 × 22	0.7	6	55 × 23	0.5
2	200	70 × 45 × 22	1	6	55 × 23	0.7
3	250	80 × 55 × 24	1.3	8	72 × 30	1
4	300	80 × 55 × 24	1.5	8	72 × 30	1.2
5	350	90 × 58 × 27	2.1	9.5	85 × 34	1.35
6	400	102 × 72 × 30	2.6	9.5	110 × 36	1.5
7	450	102 × 72 × 30	3.6	13	110 × 36	2
8	500	130 × 95 × 45	4.5	13	110 × 36	2.5
9	600	130 × 95 × 45	8	13	110 × 36	3
10	750	165 × 113 × 55	10	16	140 × 60	5.5
11	1000	210 × 140 × 80	16	16	165 × 60	8
12	1500	270 × 175 × 100	25	19	200 × 65	13
13	2000	320 × 190 × 100	37	—	—	—