




基本情報

Basic information



用途: ●製品、部品等の精密直角度測定

特長: ●JIS B 7526準拠品 ●焼入品 ※片面が両刃の薄刃になっております。

材質: ●炭素工具鋼 焼入硬度 HV450(HS60)以上

直角度: $\pm(2+L/100)\mu\text{m}$ ※Lは呼寸法を表す。

KNIFE-EDGE STANDARD SQUARE(Type III)

Application: ●Precision measurement of the squareness of products and parts

Features: ●JIS B 7526 compliant ●Hardened Both sides of the blade are sharp.

Materials: ●Carbon tool steel Quenching hardness HV450(HS60) or more

Squareness: $\pm(2+L/100)\mu\text{m}$ "L" is the nominal size.

呼寸法 Nominal size (mm)	寸法 Size (mm)			
	長片全長 Overall length, long side	短片全長 Overall length, short side	巾 Width	厚 Thickness
●50	50	40	15	4
●75	75	50	20	5
●100	100	70	25	6
●150	150	100	30	8
●200	200	130	35	10
●250	250	160	35	7
●300	300	200	40	15
●400	400	250	40	18
●500	500	250	50	20

●JIS規格外寸法 ●Nonstandard JIS size

標準価格表

品番	寸法(mm)	標準・価格(税込)	JANコード	重量(kg)
153-50	50	68,200	4560379756435	0.02
153-75	75	91,300	4560379756442	0.08
153-100	100	107,800	4560379756459	0.14
153-150	150	158,180	4560379756466	0.35
153-200	200	-	4560379756473	0.7
153-250	250	-	4560379764621	1.2
153-300	300	-	4560379756480	1.7
153-400	400	-	4560379756497	4.2
153-500	500	-	4560379756503	5.1