

品番 : OS-159A

勝手スコヤー 右



SQUARE (RIGHT)

基本情報

Basic information

| 寸法 Size (mm) | | | | | |
|--------------------------------------|---------------------------|-------------------------------|---------------------------------------|----------------------------|--------------------------------|
| 長片全長 Overall length, long side | 長片中 Width long side | 長片厚 Thickness long side | 短片全長 Overall length, short side | 短片中 Width short side | 短片厚 Thickness short side |
| 50 | 16 | 2.5 | 30 | 12 | 9 |
| 75 | 16 | 2.5 | 50 | 16 | 9 |
| 100 | 19 | 3 | 70 | 19 | 12 |
| 125 | 22 | 3 | 80 | 19 | 12 |
| 150 | 25 | 3 | 100 | 25 | 16 |
| 200 | 30 | 3 | 130 | 32 | 16 |
| 250 | 30 | 3 | 165 | 32 | 19 |
| 300 | 32 | 3 | 200 | 32 | 19 |
| 350 | 38 | 4.5 | 200 | 38 | 22 |
| 400 | 38 | 4.5 | 200 | 38 | 22 |
| 450 | 44 | 4.5 | 250 | 38 | 22 |
| 500 | 44 | 6 | 300 | 50 | 25 |
| 600 | 50 | 6 | 350 | 50 | 30 |
| 750 | 55 | 6 | 400 | 55 | 50 |
| 900 | 65 | 9 | 500 | 75 | 50 |
| 1000 | 65 | 9 | 550 | 75 | 50 |

◆呼寸法600mm以上は現在、生産見合わせ品、在庫分のみ販売となります、在庫に関しては、各営業所にご確認下さい

用途: ●直角度の測定に使用します。

特徴: ●右の側面に長片取付 ●各寸法・直角度OS-148A同等

材質: ●軟鉄

●JIS B 7526準拠品

直角度: 1級 $\pm(10+L/20)\mu\text{m}$ L=呼寸法

Application: ●Used to measure squareness.

Features: ●The blade is installed on the right side of the base. ●The dimensions and squareness are the same as item OS-148A.

Materials: ●Mild steel

●JIS B 7526 compliant

Squareness: JIS class 1 $\pm(10+L/20)\mu\text{m}$ ※"L" is the nominal size.

1級価格表

| 品番 | 寸法(mm) | 標準・価格(税込) | JANコード | 重量(kg) |
|-------------|--------|-----------|--------|--------|
| 159A-50L1 | 50 | 7,480 | | 0.08 |
| 159A-75L1 | 75 | 7,480 | | 0.1 |
| 159A-100L1 | 100 | 8,316 | | 0.15 |
| 159A-125L1 | 125 | 9,680 | | 0.3 |
| 159A-150L1 | 150 | 10,406 | | 0.5 |
| 159A-200L1 | 200 | 13,420 | | 0.7 |
| 159A-250L1 | 250 | 18,480 | | 0.9 |
| 159A-300L1 | 300 | 21,340 | | 1.5 |
| 159A-350L1 | 350 | 35,200 | | 1.7 |
| 159A-400L1 | 400 | 38,280 | | 2.5 |
| 159A-450L1 | 450 | 67,100 | | 3.5 |
| 159A-500L1 | 500 | 77,000 | | 5.4 |
| 159A-600L1 | 600 | 120,120 | | 6.5 |
| 159A-750L1 | 750 | 212,520 | | 14 |
| 159A-900L1 | 900 | 335,060 | | 26 |
| 159A-1000L1 | 1000 | 369,600 | | 29 |